

FH – PVC – supported

High rise - travelling height maximum 400m



Drawing according to article number 161448 - Type 8292-F



Beschrijving

Elevator suspension cable for indoor and panoramic elevators

Toepassing

To comply with the correct installation procedures please refer to the Datwyler installation manual which is available separately

Constructie

Ader isolatie	PVC
Buitenmantel	PVC
Core flexibel	class 5
Mantelkleur	grijs
Ondersteunende leden	ST = Steel, diameter in [mm]

Algemene eigenschappen

Bedrijfstemperatuur	-15 °C - +70 °C
Coax	grijs
Kern	black, white numbered, G = with green-yellow core(s)
Pair/quad	various colours or black with white numbers

Elektrische eigenschappen

Nominale spanning Uo/U	according to table
------------------------	--------------------

Mechanische eigenschappen

Aanbevolen lusdiameter	according to table, tolerance -50/+100 mm
Maximale loopsnelheid	12 m/s
Maximale reishoogte	400 m
Maximale vrije schorsing	220 m
Versnelling	1,2 m/s ²

Normen / Standards

Standaard voor flexibele besturingskabels voor liften	EN 50214
---	----------

Versions

Materiaal nummer	Artikel	Mantelkleur	Cu tarief [kg\km]	Gewicht [kg\km]
157219	7877-F	grijs	309	1.099
185284	7877-F	grijs	446	1.597
161448	8292-F	grijs	400	1.372

Onder voorbehoud van technische wijziging

Vanaf 2020-12-15 10:05:20